

# SELF-DRILLING SCREWS

DEC also introduces an assortment of **SELF-DRILLING SCREWS** in order to process DEC products.



## CONSTRUCTION.

The screws have been produced out of galvanized steel. The screw thread continues up to the head. The tail of the screw has been provided with a drill head. So pre-drilling is not necessary.

Associated bits are also available.  
Each 1000 screws 1 bit.

2.16

## DELIVERY PROGRAM.

The **self-drilling screws** are available in different sizes.

## ORDERING INFORMATION.

DEC's delivery program includes the following **self-drilling screws** and **bits**:

Ordering code	Sizes (mm x mm)	Maximum thickness of plate
SCR3.5/13	3.5 x 13	2.3 mm
SCR3.5/9.5	3.5 x 9.5	2.3 mm
SCR4.2/13	4.2 x 13	3.4 mm
SCR4.2/16	4.2 x 16	3.4 mm
SCR4.2/19	4.2 x 19	3.4 mm
SCR4.2/25	4.2 x 25	3.4 mm
SCR4.2/32	4.2 x 32	3.4 mm
SCR4.2/40	4.2 x 40	3.4 mm
SCR4.2/50	4.2 x 50	3.4 mm
SCR4.8/16	4.8 x 16	4.5 mm
SCR4.8/19	4.8 x 19	4.5 mm
SCR4.8/25	4.8 x 25	4.5 mm
SCRBIT N°. 1	3.5 mm	Irrelevant
SCRBIT N°. 2	4.2 and 4.8 mm	Irrelevant

The information contained in this brochure was current on the publication date. The Company reserves the right to make changes in details at any time without prior notice. In order to avoid misunderstandings, any interested party is advised to contact the Company checking for any changes in materials and/or information after this brochure was published.

Version 2003 WWW.DECINTERNATIONAL.COM