

SMOKEDEC



The **SMOKEDEC** is an efficient and a simple tool to visualize, movements of air such as leakage of ventilation systems and chimneys.

- ▶ Air flow around grids during balancing of the A/C system.
- ▶ Leakage in a high-pressure hose.
- ▶ Checking the flow of chimney's.
- ▶ Controlling of boilers.
- ▶ Conserving energy: draught from doors and windows.

FUNCTION

Each cartridge emits generous amount of greyish-white smoke with almost the same density as air to be able to visualize movements of air streams without rising or falling. The greyish-white colour is visible, even in dark corners. The smoke is ionized and oil-free and is emitted in a constant stream

INSTRUCTION.

Place one smokedec cartridge on a non combustable place. Light up the cartridge for the choosen smoking time.

Never use SMOKEDEC unattended.

WARNING

Use this product ONLY in a professional way (see instructions). Avoid any contact and inhaling of the smoke. The room must be ventilated properly afterwards. Keep product under lock and key.

Preventing measurements:

- Possibility to rinse eyes.
- Using gloves.
- Keep fire extinguisher stand-by.

Smokedec	Burningtime	Smokevolume	Weight of 1 cartr.	In pack of
SM045	45 sec / 0.75 min	5 m ³ /h	3 Gr	10 x10
SM090	90 sec / 1.5 min	17 m ³ /h	10 Gr	10 x 10
SM150	150 sec / 2.5 min	35 m ³ /h	20 Gr	10 x 5
SM240	240 sec / 4 min	70 m ³ /h	58 Gr	10 x 5
SM300	300 sec / 5 min	500 m ³ /h	454 Gr	6 x1

The information contained in this brochure was current on the publication date (01-2004). The Company reserves the right to make changes in details at any time without prior notice. In order to avoid misunderstandings, any interested party is advised to contact the Company checking for any changes in materials and/or information after this brochure was published.

Version 2004. WWW.DECINTERNATIONAL.COM