


FS2000/DEC050

The combination of **FS2000/DEC050** is easily applied and suitable for use on High/Medium/Low Pressure Interior galvanised systems of spiral wound ducting, rectangular ducting and plenums. It is also effective and has a good adhesion on plastic, wood, glass, plaster, cement and on most porous materials. Torn and damaged lagging can also be repaired to give a permanent cover. **FS2000/DEC050** provides a 100% air tight seal.



CONSTRUCTION

FS2000/DEC050 are two components, making a sealing together. **DEC050** is a minimally impregnated tape and **FS2000** is a liquid binder. If the binder is attached to the tape the construction will be smooth.

DELIVERY PROGRAM

FS2000/DEC050 is available in two different standard packagings. Standard length of a roll of tape is 90 m with a width of 75 mm. The standard packaging contains 5 rolls of tape. The binder is available in a 5 litre can. A standard packaging contains 3 cans.

Ordering code binder: **FS2000**
Ordering code tape: **DEC 050**

CONSUMPTIVE USE

Approximately 2.5 litres of binder per roll tape.

OPERATION TEMPERATURE

FS2000/DEC050 is suitable for application within the following temperature range: -30 +100°C.

The processing has to take place between +5 and +30°C

OPERATION PRESSURE

FS2000/DEC050 is suitable up to an over pressure of +5000 Pa. A pressure resistance of +30.000 Pa can be attained if more layers are used.

DRYING TIME

Within a period of 4 up to 72 hrs the **FS2000/DEC050** will be completely hard. The accurate time depends on the prevailing temperature and the air humidity.

ADHESIVE

The combination of **FS2000/DEC050** adheres to: steel, plastics, woods, textiles, ceramic products, glass, cement etc.

The adhesion result hardly depends on the condition of the surface (concerning fat and dirt).

FIRE RESISTANCE

After testing **FS2000/DEC050** has been classified into class B1, according to DIN4102 (Germany)

STORAGE

FS2000/DEC050 has a lifespan of five 5 years if the packaging is sealed and the storage room is frost-resisting.

TOXICITY

FS2000/DEC050 is non toxic in both the 'wet' and 'dry' condition.

The information contained in this brochure was current on the publication date. The Company reserves the right to make changes in details at any time without prior notice. In order to avoid misunderstandings, any interested party is advised to contact the Company checking for any changes in materials and/or information after this brochure was published.

Version 2003. WWW.DECINTERNATIONAL.COM