

Valve actuator 1000 N



RVA10 is a series of medium force valve actuators. RVA10 valve actuators are available in different versions with either a 3-point signal, 0...10 V DC or 2...10 V DC. The valve actuators with 0...10 V DC or 2...10 V DC control signals are equipped with automatic self stroke adjustment. All actuators in the RVA series can be operated manually.

Technical data	
Supply voltage	24 V AC
Control signal	3-point, 0...10 V DC or 2...10 V DC
Power consumption	Max 6 VA
Stroke	20 mm fixed, 10...30 mm, self stroke adjustment (for analogue output only)
Stroke time	3 s/mm
Protection class	IP54

Description	Control signal	Supply voltage	Force	Type	Notes
Valve actuator	3-point	24 V AC	1000 N	RVA10-24	
Valve actuator	0...10 V DC or 2...10 V DC	24 V AC	1000 N	RVA10-24A	

Valve actuators 1800 N



RVA18 is a series of high force valve actuators. RVA18 valve actuators are available in different versions, with either a 3-point signal, 0...10 V DC or 2...10 V DC. The valve actuators with 0...10 V DC or 2...10 V DC control signals are equipped with automatic self stroke adjustment. All actuators in the RVA series can be operated manually.

Technical data	
Supply voltage	24 V AC
Control signal	3-point, 0...10 V DC or 2...10 V DC
Power consumption	Max 8 VA
Stroke	40 mm fixed, 10...52 mm, self stroke adjustment (for analogue output only)
Stroke time	3 s/mm
Protection class	IP54

Description	Control signal	Supply voltage	Force	Type	Notes
Valve actuator	3-point	24 V AC	1800 N	RVA18-24	
Valve actuator	0...10 V DC or 2...10 V DC	24 V AC	1800 N	RVA18-24A	

Valve actuator 2500 N



RVA25 is a series of high force valve actuators. RVA25 valve actuators are available in different versions with either a 3-point signal, 0...10 V DC or 2...10 V DC. The valve actuators with 0...10 V DC or 2...10 V DC control signals are equipped with automatic self stroke adjustment. All actuators in the RVA series can be operated manually.

Technical data	
Supply voltage	24 V AC
Control signal	3-point, 0...10 V DC or 2...10 V DC
Power consumption	Max 12 VA
Stroke	40 mm fixed, 10...52 mm, self stroke adjustment (for analogue output only)
Stroke time	3 s/mm
Protection class	IP54

Description	Control signal	Supply voltage	Force	Type	Notes
Valve actuator	3-point	24 V AC	2500 N	RVA25-24	
Valve actuator	0...10 V DC or 2...10 V DC	24 V AC	2500 N	RVA25-24A	