

Valve for Honeywell actuators



3-way

The valves below are intended for use in heating and ventilation systems together with Honeywell actuators.

Technical data	
Valve flow type	Square
Fluid temperature	-5...+185°C
Media	Hot, cold, glycol mixed water (max 50%) or steam
Connection	Metric female threaded
Rangeability	50:1
Stroke	20 mm
Pressure rating	PN16
Material	
Body	Rg5 (gun metal SS 5204)
Plug	Rg5 (gun metal SS 5204)
Stem	Stainless steel
Packing box	Auto adjusted, teflon (O-ring Viton)

Description	Connection	Max diff. pressure	Kvs	Art. No	Type	Notes
3-way valve	DN15	1.6 MPa	2.1	29273800159014	V538C3057	
3-way valve	DN20	1.6 MPa	4.2	29273800209006	V538C3055	
3-way valve	DN25	1.6 MPa	8.6	29273800259000	V538C3156	
3-way valve	DN32	1.0 MPa	14	29273800329016	V538C3209	
3-way valve	DN40	0.8 MPa	20	29273800409012	V538C3252	
3-way valve	DN50	0.5 MPa	34	29273800509013	V538C3301	

Valve for Honeywell actuators



3-way

Flanged valves intended for continuous control of cold/hot water and steam together with Honeywell actuators.

Technical data	
Valve flow type	Square
Media	Hot, cold, glycol mixed water or steam
Fluid temperature	-5...+120°C
Max. leakage	0.1% of Kvs
Rangeability	50:1
Pressure rating	PN16
Material	
Body	Cast iron SS 0120
Plug & seat	Gun metal SS 5204
Stem, cone	Stainless steel SS 2346
Packing box	Self-adjusting teflon
O-ring	Viton
Bonnet	Brass SS 5170
Seal flange	Steel SS 2172

Description	Connection	Max diff. pressure	Kvs	Art. No	Type	Notes
3-way valve	DN50	1.0 MPa	34	29563800509013	V538C6304	
3-way valve	DN65	0.6 MPa	55	29563800659000	V538C6356	
3-way valve	DN80	0.4 MPa	80	29563800809000	V538C6408	
3-way valve	DN100	0.25 MPa	130	29563801009000	V538C6459	
3-way valve	DN125	0.16 MPa	215	29563801259000	V538C6500	
3-way valve	DN150	0.11 MPa	310	29563801509000	V538C6551	