

Zone valves

Zone valves intended for use together with actuators MVT44 and MVT57.



2-way



3-way

Technical data	
Flow characteristics	equal percentage A-AB port, linear B-AB for Kvs 0.24 to 2.5, equal percentage A-AB port, linear B-AB for Kvs 4 and Kvs 6
Fluid temperature	2...95°C
Media	Warm or cold water. Also water mixed with glycol (Max 30%)
Connection	male threaded
Rangeability	50:1
Material housing	Brass
Stroke	5.5 mm
Pressure rating	PN16

Description	Connection	Max diff. pressure	Kvs	Type	Notes
2-way valve	DN15	350 kPa	0.25	VSXT09P	
2-way valve	DN15	350 kPa	0.4	VSXT10P	
2-way valve	DN15	350 kPa	0.6	VSXT11P	
2-way valve	DN15	350 kPa	1.0	VSXT12P	
2-way valve	DN15	350 kPa	1.6	VSXT13P	
2-way valve	DN15	250 kPa	2.0	VSXT1P	
2-way valve	DN15	250 kPa	2.5	VSXT21P	
2-way valve	DN20	150 kPa	4.0	VSXT24P	
2-way valve	DN25	150 kPa	6.0	VSXT26P	
3-way valve	DN15	350 kPa	0.25	VMXT09P	
3-way valve	DN15	350 kPa	0.4	VMXT10P	
3-way valve	DN15	350 kPa	0.6	VMXT11P	
3-way valve	DN15	350 kPa	1.0	VMXT12P	
3-way valve	DN15	350 kPa	1.6	VMXT13P	
3-way valve	DN15	250 kPa	2.0	VMXT1P	
3-way valve	DN15	250 kPa	2.5/1.6	VMXT21P	
3-way valve	DN20	100/40 kPa*	4.0	VMXT24P	
3-way valve	DN25	100/40 kPa*	6.3	VMXT26P	

* First value for straight-through port, second value for angled port.